

APPROXIMATE COVERAGE GUIDE

Coverage given is approximate only. Actual coverage may vary.

General Material Weights		
Ontario limestone	165 lbs/ft ³	
Indiana limestone	145 lbs/ft ³	
North American limestone	155 lbs/ft ³	
Granite	175 lbs/ft ³	

Armourstone	coverage*
Buckhorn, Northern Brown	6 to 8 ft²/ton
Flamboro, Orillia	4 to 6 ft ² /ton

*Based on a 2' x 2' x 3' piece equalling 1 ton

Flagstone	weight*	coverage
½" to ¾" thick	9 lbs/ft ²	250 ft ² /ton
1" thick	14 lbs/ft ²	150 ft²/ton
1½" thick	21 lbs/ft ²	100 ft²/ton
2" thick	28 lbs/ft ²	80 ft²/ton
3" to 4" thick	50 lbs/ft ²	40 ft²/ton
6" to 7" thick	90 lbs/ft ²	23 ft ² /ton

*Based on Ontario limestone

Building & Wall Stone	weight	coverage
4" building stone	50 lbs/ft ²	40 ft ² /ton
8" wall stone	100 lbs/ft ²	20 ft ² /ton

Aggregates

 $1 \text{ yard} = 27 \text{ ft}^{3}$

Decorative aggregates (a.k.a. pebble): min. depth to achieve coverage = stone diameter x 1.6

Mortar		
brick sand : type S/N cement ratio	3:1	
1/2 yard of brick sand requires 5-6 bags of type S or N cement		
1 bag of type S or N cement requires 3-4 brick sand	poly bags of	